HK:+852-69575415 China GuangDong:+13538586433 ShangHai:+18816996168

TEKNOR APEX

SINPOLENE MBB7511

新加坡聚合树脂有限公司 - 聚乙烯

一般信息

产品说明

SINPOLENE MBB7511 is a masterbatch based on a furnace carbon black dispersed in polyethylene. It is designed specifically for use in general film, mulch film, extrusion of sheet and injection molding of polyethylene.

SINPOLENE MBB7511 is delivered as free flowing pellets for processing convenience. The product should be stored in dry place.

CHARACTERISTICS

* Easy processing
* Good dispersion
* Higher jetness
* Good weather and UV light protection
* Minimal wear effect on processing equipment

总览

材料状态	• 已商用：当前有效	
供货地区	• 亚太地区	
特性	• 通用	
用途	• 薄膜	• 片材
RoHS 合规性	• RoHS 合规	
外观	• 黑色	
形式	• 粒子	
加工方法	• 吹塑薄膜	• 挤出

ASTM & ISO 属性[1]

物理性能	额定值	单位制	测试方法
密度 / 比重	1.16		ASTM D792
熔流率（熔体流动速率）	20 到 80	g/10 min	ASTM D1238
炭黑含量	38 到 42	%	ASTM D1603
含水量	< 0.25	%	ASTM D3030

补充信息

Recommended dosage 2 - 5%

备注

[1] 一般属性：这些不能被视为规格。