

超塑烯® UE33002

EVATHENE® UE33002

乙烯醋酸乙烯酯共聚合樹脂

Ethylene-Vinyl Acetate Copolymer Resins



概述

Description

超塑烯® UE33002 是一種乙烯醋酸乙烯酯共聚合樹脂，可運用於電線電纜摻合樹脂。

EVATHENE® UE33002 is an ethylene-vinyl acetate copolymer resin (EVA) for use in wire and cable compounds.

特性

Characteristics

- ◇ 柔軟
- ◇ 彈性
- ◇ 低溫柔軟性很好
- ◇ 黏著力優異

- ◇ Flexibility
- ◇ Elasticity
- ◇ Low temperature flexibility
- ◇ Excellent adhesion

應用

Applications

1. 電線電纜摻合樹脂

1. Wire and cable compounds

物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
VA 含量 VA Content (%)	USI	33
熔融指數 Melt Index (g/10min)	ASTM D1238	0.2
密度 Density (g/cm ³)	ASTM D792	0.956
斷裂點抗張強度(模片) Tensile Strength at Break (Molded) (kg/ cm ²)	ASTM D638	170
斷裂點伸長率 (模片) Ultimate Elongation at Break (Molded) (%)	ASTM D638	710
環球軟化溫度 Ring&Ball Softing Temperature(°C)	ASTM E28	-
熔點 Melting Point (°C)	ASTM D3418	64
硬度(蕭氏 A) Hardness (Shore A)	ASTM D2240	70