

超塑烯® UE4003

EVATHENE® UE4003

乙烯醋酸乙烯酯共聚合樹脂

Ethylene-Vinyl Acetate Copolymer Resins



概述

Description

超塑烯® UE4003 是一種高 VA 含量的乙烯醋酸乙
烯酯共聚合樹脂，可運用於注塑與模壓發泡成型
設備。

EVATHENE® UE4003 is an ethylene-vinyl acetate
copolymer resin (EVA) with high VA content for use in
foam injection and compression molding machine.

特性

Characteristics

- ◇ 柔軟
- ◇ 彈性
- ◇ 低溫柔軟性很好
- ◇ 黏著力優異

- ◇ Flexibility
- ◇ Elasticity
- ◇ Low temperature flexibility
- ◇ Excellent adhesion

應用

Applications

1. 鞋材發泡
2. 電線電纜摻合樹脂

1. Shoe sole foaming
2. Wire and cable compounds

物理性質 Physical Properties

項 目 Properties	試 驗 方 法 Test Method	數 值 Typical Value
VA 含量 VA Content (%)	USI	40
熔融指數 Melt Index (g/10min)	ASTM D1238	3
密度 Density (g/cm ³)	ASTM D792	0.967
斷裂點抗張強度(模片) Tensile Strength at Break (Molded) (kg/cm ²)	ASTM D638	81
斷裂點伸長率(模片) Ultimate Elongation at Break (Molded) (%)	ASTM D638	>1000
環球軟化溫度 Ring&Ball Softening Temperature(°C)	ASTM E28	-
熔點 Melting Point (°C)	ASTM D3418	48
硬度(蕭氏 A) Hardness (Shore A)	ASTM D2240	43